



ACP

Asiatic Chemicals Pakistan

Building the Partnership, it's Asiatic Business Principle!

Address : Room No 30, 2nd Floor, Mussa Market Opp Sindh Madresha, Shahrah-e-Liaquat Karachi, Pakistan.**Phone :** 92-21-2422537, (Hunting line) 2420313**Fax :** 92-21-2415544 , 0092-300-2022068**Mobile :** 92-300-2000881, 92-321-2000881

Material Safety Data Sheet

According to 91/155 EEC

Printing date 03.08.2006

Reviewed on 24.07.2006

1 Identification of the substance/preparation and of the company/undertaking

- **Product details**
- **Trade name:** Methyl Ethyl Ketone
- **Manufacturer/Supplier:**
Petrochem Middle East FZE
PO Box 17028,
Jebel Ali Free Zone
Dubai, UAE
Ph +971 4 8839222; Fax +971 4 8834133
- **Further information obtainable from:** Product safety department.

2 Composition/information on ingredients

- **Chemical characterization:**
- **CAS No. Description**
78-93-3 butanone
- **Identification number(s)**
- **EINECS Number:** 201-159-0
- **EU Number:** 606-002-00-3

3 Hazards identification

- **Hazard description:**



Xi Irritant
F Highly flammable

- **Information concerning particular hazards for human and environment:**
At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.
R 11 Highly flammable.
R 36 Irritating to eyes.
R 66 Repeated exposure may cause skin dryness or cracking.
R 67 Vapours may cause drowsiness and dizziness.

4 First aid measures

- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.

5 Fire-fighting measures

- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Protective equipment:** No special measures required.

Material Safety Data Sheet

According to 91/155 EEC

Printing date 03.08.2006

Reviewed on 24.07.2006

Trade name: Methyl Ethyl Ketone

(Contd. of page 1)

6 Accidental release measures

- **Person-related safety precautions:** Wear protective equipment. Keep unprotected persons away.
- **Measures for environmental protection:** Do not allow to enter sewers/ surface or ground water.
- **Measures for cleaning/collecting:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.

7 Handling and storage

- **Handling:**
- **Information for safe handling:** No special requirement
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep container tightly sealed.
Store in cool, dry conditions in well sealed receptacles.

8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

- **Ingredients with limit values that require monitoring at the workplace:**

78-93-3 butanone

PEL (USA)	590 mg/m ³ , 200 ppm
REL (USA)	Short-term value: 885 mg/m ³ , 300 ppm Long-term value: 590 mg/m ³ , 200 ppm
TLV (USA)	Short-term value: 885 mg/m ³ , 300 ppm Long-term value: 590 mg/m ³ , 200 ppm BEI
TLV (EU)	Short-term value: 900 mg/m ³ , 300 ppm Long-term value: 600 mg/m ³ , 200 ppm
WEL (Great Britain)	Short-term value: 899 mg/m ³ , 300 ppm Long-term value: 600 mg/m ³ , 200 ppm

- **Additional information:** The lists valid during the making were used as basis.

- **Personal protective equipment:**

- **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Avoid contact with the eyes.

Avoid contact with the eyes and skin.

- **Respiratory protection:** Not required.

- **Protection of hands:**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Contd. on page 3)

Material Safety Data Sheet

According to 91/155 EEC

Printing date 03.08.2006

Reviewed on 24.07.2006

Trade name: Methyl Ethyl Ketone

(Contd. of page 2)

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **General Information**

Form:	Fluid
Colour:	Colourless
Odour:	Pleasant

· **Change in condition**

Melting point/Melting range: -86.3°C
Boiling point/Boiling range: 79-80.5°C

· **Flash point:** -4°C

· **Ignition temperature:** 514°C

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· **Explosion limits:**

Lower:	1.8 Vol %
Upper:	11.5 Vol %

· **Vapour pressure at 20°C:** 105 hPa

· **Density at 20°C:** 0.804-0.807 g/cm³

· **Solubility in / Miscibility with water at 20°C:**

290 g/l

· **Viscosity:**

Dynamic at 15°C: 0.423 mPas

10 Stability and reactivity

· **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.

· **Dangerous reactions** No dangerous reactions known.

· **Dangerous decomposition products:** No dangerous decomposition products known.

UAE

(Contd. on page 4)

Material Safety Data Sheet

According to 91/155 EEC

Printing date 03.08.2006

Reviewed on 24.07.2006

Trade name: Methyl Ethyl Ketone

(Contd. of page 3)

11 Toxicological information

· **Acute toxicity:**

· **LD/LC50 values relevant for classification:**

Oral	LD50	3300 mg/kg (rat)
Dermal	LD50	5000 mg/kg (rabbit)

· **Primary irritant effect:**

· **on the skin:** No irritant effect.

· **on the eye:** Irritating effect.

· **Sensitization:** No sensitizing effects known.

12 Ecological information

· **General notes:**

Water hazard class 1 (German Regulation) (Assessment by list): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

13 Disposal considerations

· **Product:**

· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packaging:**

· **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· **Land transport ADR/RID (cross-border)**



· **ADR/RID class:** 3 Flammable liquids.

· **Danger code (Kemler):** 33

· **UN-Number:** 1193

· **Packaging group:** II

· **Hazard label:** 3

· **Description of goods:** 1193 ETHYL METHYL KETONE (METHYL ETHYL KETONE)

· **Maritime transport IMDG:**



· **IMDG Class:** 3

· **UN Number:** 1193

· **Label:** 3

· **Packaging group:** II

· **EMS Number:** F-E,S-D

(Contd. on page 5)

Material Safety Data Sheet
According to 91/155 EEC

Printing date 03.08.2006

Reviewed on 24.07.2006

Trade name: Methyl Ethyl Ketone

(Contd. of page 4)

· **Proper shipping name:** ETHYL METHYL KETONE (METHYL ETHYL KETONE)

· **Air transport ICAO-TI and IATA-DGR:**



· **ICAO/IATA Class:** 3

· **UN/ID Number:** 1193

· **Label:** 3

· **Packaging group:** II

· **Proper shipping name:** ETHYL METHYL KETONE (METHYL ETHYL KETONE)

15 Regulatory information

· **Labelling according to EU guidelines:**

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· **Code letter and hazard designation of product:**

Xi Irritant

F Highly flammable

· **Risk phrases:**

11 Highly flammable.

36 Irritating to eyes.

66 Repeated exposure may cause skin dryness or cracking.

67 Vapours may cause drowsiness and dizziness.

· **Safety phrases:**

2 Keep out of the reach of children.

9 Keep container in a well-ventilated place.

16 Keep away from sources of ignition - No smoking.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing MSDS:** Product safety department.

· **Contact:** Terminal Manager

UAE